

## Automatic stretch film rewinder



The automatic stretch film rewinder mod. **RES-08** is characterized by an extreme ease of use and high versatility in production.

The machine is made of first class components and is able to produce **stretch film** hand rolls, machine rolls and **cling film** rolls. The machine produces rolls with different core diameters, in order to easily satisfy the market requirements, which are continuously evolving.

The RES-08 grants low production costs, thanks to its exclusive **ERS - Energy Recovery System** and quick change of rolls.

All manual operations, including maintenance, can be done even by inexperienced operators.

RES-08 has Remote control & Data logging and is **industry 4.0 ready**.

# RES-08

## Products

Stretch film hand rolls

Stretch film machine rolls

Cling film rolls



## Technical features

Max. material width: **600 mm**

Min. material width: **300 mm**

Max. diameter mother roll: **500 mm**

Max. diameter finished roll: **250 mm**

Material thickness: **5-35 micron**

Max. rewinding speed: **1700 m/min**

Internal cores diameter: **26-76 mm**

Production cycle time:

**9,9 sec** (for 150 m rolls)

**12,2 sec** (for 200 m rolls)

**13,5 sec** (for 250 m rolls)



**Top Speed**  
**upto 1700 m/min!**

The fastest rewinding machine for stretch film on the Market, thanks to our innovative **ERS - Energy Recovery System**, reduces electrical consumption upto 27%.

### Maklaus s.r.l.

Località Piani della Rugginosa 236/237 - 50066 Reggello (FI), Italia  
www.maklaus.com | Sales Office Tel. +39 03311550146  
commerciale@maklaus.com | Head Office Tel. +39 0550456700

# Maklaus